



# CERTIFICATION LICENCE TO USE KEYMARK

Certificate No OEM 9999.1.18

*DQS Hellas grants the present certificate to the enterprise:*

**LAMINOX SRL**

Zona Industriale Callarella 261-263, 62028 Sarnano (MC), Italy

*for the product:*

**Flat plate Solar Collectors with type**

SSC-FM-1.50, SSC-FM-1.50H, SSC-FM-1.82, SSC-FM-1.82H, SSC-FM-2.00, SSC-FM-2.00H,  
SSC-FM-2.37, SSC-FM-2.37H, SSC-FM-2.72, SSC-FM-2.72H

*which is produced in conformity with the normative document:*

**EN 12975-1:2011**

**EN ISO 9806:2013**

*at the following location:*

**1o Km Inofyta – St. Thomas  
32011 Viotia**



**E 31**



*The present certificate is granted in accordance with:*

- *the DQS Hellas General Rules for the Certification of Products,*
- *the Specific Rule for Certification EKIII.001 «Specific Rule for Certification of Solar Collectors, and Thermal Solar Heating Systems for Domestic Hot Water»,*
- *the Specific CEN Keymark Scheme Rules for Solar Thermal Products,*

*and is ruled by the terms of the relevant contract between DQS Hellas and the enterprise.*

*Date of issue:* 2023-11-30

*Date of valid:* 2024-11-30

**Ioannis Alexiou**  
*Head of Products Certification*

**Panagiotis Giannoutsos**  
*Director of Certification*





# CERTIFICATION LICENCE TO USE KEYMARK

Certificate No OEM 9999.2.11

*DQS Hellas grants the present certificate to the enterprise:*

**LAMINOX SRL**

Zona Industriale Callarella 261-263, 62028 Sarnano (MC), Italy

*for the product:*

**Flat plate Solar Collectors with type**

**SSC-FM-2.72, SSC-FM-2.72H**

*which is produced in conformity with the normative document:*

**EN 12975-1:2011**

**EN ISO 9806:2013**

*at the following location:*

**1o Km Inofyta – St. Thomas  
32011 Viotia**



**E 31**



*The present certificate is granted in accordance with:*

- *the DQS Hellas General Rules for the Certification of Products,*
- *the Specific Rule for Certification EKIII.001 «Specific Rule for Certification of Solar Collectors, and Thermal Solar Heating Systems for Domestic Hot Water»,*
- *the Specific CEN Keymark Scheme Rules for Solar Thermal Products,*

*and is ruled by the terms of the relevant contract between DQS Hellas and the enterprise.*

*Date of issue:* **2023-11-30**

*Date of valid:* **2024-11-30**

**Ioannis Alexiou**  
*Head of Products Certification*

**Panagiotis Giannoutsos**  
*Director of Certification*











<b>Annex to Solar Keymark Certificate</b> <b>Supplementary Information</b>	<b>Licence Number</b>	<b>OEM 9999.2.11</b>
	<b>Issued</b>	<b>2023-11-30</b>

Gross Thermal Yield in kWh/collector at mean fluid temperature $\vartheta_m$													
Collector name	Standard Locations	Athens			Davos			Stockholm			Würzburg		
	$\vartheta_m$	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
SSC-FM-2.72		3.422	2.564	1.786	2.673	1.943	1.310	1.954	1.349	874	2.121	1.461	932
SSC-FM-2.72H		3.422	2.564	1.786	2.673	1.943	1.310	1.954	1.349	874	2.121	1.461	932
Gross Thermal Yield per m <sup>2</sup> gross area		1.258	942	657	983	714	482	718	496	321	780	537	343
Annual efficiency, $\eta_a$		71%	53%	37%	60%	44%	30%	62%	43%	28%	63%	43%	28%
Fixed or tracking collector	Fixed (slope = latitude - 15°; rounded to nearest 5°)												
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1630 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>			1244 kWh/m <sup>2</sup>		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature  $\vartheta_m$  (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at <http://www.estif.org/solarkeymarknew/>

Additional Information			
Collector heat transfer medium	Water-Glycole		
The collector is deemed to be suitable for roof integration	No		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)	A		--
G (W/m <sup>2</sup> ) >	1000	$\vartheta_a$ (°C) >	20
		$H_x$ (MJ/m <sup>2</sup> ) >	600
Maximum tested positive load	3000		Pa
Maximum tested negative load	3000		Pa
Hail resistance using steel ball (maximum drop height)	2		m

Additional collector attribute(s)			
Using external power source(s) for normal operation	No	Active or passive measure(s) for self-protection	No
Co-generating thermal and electrical power	No	Façade collector(s)	No

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, $A_{sol}$ (m <sup>2</sup> )	Hydraulic Designation Code	Aperture Area, $A_a$ (m <sup>2</sup> )
SSC-FM-2.72	2,72	11-V-1234S-A:7.2,2060-C:20.6,1320-	2,57
SSC-FM-2.72H	2,72	18-V-1234S-A:7.2,1158-C:20.6,2240-	2,57

Data required for CDR (EU) No 811/2013 - Reference Area $A_{sol}$		Data required for CDR (EU) No 812/2013 - Reference Area $A_{sol}$	
Collector efficiency ( $\eta_{col}$ )	63%	Zero-loss efficiency ( $\eta_0$ )	0,77
Remark: Collector efficiency ( $\eta_{col}$ ) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m <sup>2</sup> , expressed in % and rounded to the nearest integer. Deviating from the regulation $\eta_{col}$ is based on reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient ( $a_1$ )	3,15
		Second-order coefficient ( $a_2$ )	0,012
		Incidence angle modifier IAM (50°)	0,96
			--
Remark: The data given in this section are related to collector reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.			